

Technical characteristics

- Relative and differential pressure measurements
- Pressure range: 0 - 3 ... 100 mbar
-1.5 ... 1.5 mbar
- Accuracy <1 % fs
- Print mounting
- Temperature compensated (-10°C up to + 80°C)
- Output signals:
 - Digital: I²C and ZACWire
 - Analogue: 0.5 ... 4.5 V and ratiom. 10 ... 90%
- Dimensions: 23.2 mm x 24.5 mm x 17.8 mm

Why should type 450 be chosen ?

Measurement applications	Type 450 cantilevered technology	Silicon technology
Neutral air	✓	✓
Polluted air	✓	X
High humidity air	✓	X
Air containing small dust particles	✓	X
No filters needed	✓	X

Huba Control AG

Headquarters Schweiz
Industriestrasse 17
CH-5436 Würenlos
Telefon +41 56 436 82 00
Fax +41 56 436 82 82
info.ch@hubacontrol.com

Huba Control AG

Niederlassung Deutschland
Schlattgrabenstrasse 24
D-72141 Walldorfhäslach
Telefon +49 7127 2393 00
Fax +49 7127 2393 20
info.de@hubacontrol.com

Huba Control SA

Succursale France
Rue Lavoisier
Technopôle Forbach-Sud
F-57602 Forbach Cedex
Téléphone +33 3 87 84 73 00
Télécopieur +33 3 87 84 73 01
info.fr@hubacontrol.com

Huba Control

Huba Control AG

Vestiging Nederland
Hamseweg 20A
NL-3828 AD-Hoogland
Telefoon +31 33 433 03 66
Telefax +31 33 433 03 77
info.nl@hubacontrol.com

Huba Control USA, Inc.

Office United States of America
303 Wyman Street
Suite #300
Waltham MA 02451
Tel: +1 866-6HUBACO (+1 866-648-2226)
info.usa@hubacontrol.com

Huba Control AG

Branch Office United Kingdom
Unit 13 Berkshire House, County Park
Business Centre, Shrivenham Road
Swindon Wiltshire SN1 2NR
Phone +44 1993 77 66 67
Fax +44 1993 77 66 71
info.uk@hubacontrol.com

www.hubacontrol.com

Huba Control



Differential pressure transmitter



Type 450

Relative and differential pressure transmitter in a compact housing with digital output signal.

www.hubacontrol.com



Relative and differential pressure transmitter type 450

Huba Control has developed the new relative and differential pressure transmitter type 450 for low pressure measurements, based on the cantilevered beam technology and built in a compact housing.

The type 450 is especially suitable for polluted environments containing small dust particles. The type 450 is also available with different signal output configurations and is therefore very adaptable to the requirements of pressure measurements.

Product benefits

- ✓ Excellent accuracy (<1% fs) and long term stability
- ✓ Temperature compensated from -10°C up to +80°C
- ✓ Suitable for print mounting, compact housing
- ✓ Less influence on temperature changes
- ✓ Free of maintenance

Area of application and properties

- For low pressure measurements 0 ... 3 - 100 mbar and -1.5 ... 1.5 mbar
- Suitable for polluted air containing small dust particles
- Standard HVAC systems with air and neutral gases
- Digital output (I²C) and analogue output (ratiom. and regulated)
- Reliable and robust

Suitable for the following environments:

